



## **Cleaning of Rhino Flooring Systems & Rhino ArmaFloor® 500 DF**

1. Use a Commercial Grade foaming cleaning product such as TOPAX 686 foaming alkaline detergent (Ecolab) or CITRODET foaming cleaner (Jasol). Refer to data sheet or packaging for dilution rates.
2. Apply to the floor area and scrub with a hard bristle broom or a deck scrub, ensuring the foaming action takes place. This will lift the dirt from around the high points in the Rhino Linings flooring material. Leave to foam for 3 to 5 minutes.
3. Hose or wash off the area with cold or luke-warm water using a hose. You can use a squeegee to assist you in this process. If using a mop, be aware that some mops may leave mop fibres in the non-slip medium.

TOPAX 686 is manufactured by Ecolab and is available directly from the supplier on North Island 0508 732 733 or South Island 0508 737 343  
CITRODET is manufactured by Jasol and is available on 09 580 2105 or 03 384 4433

### **Rhino Linings New Zealand**

62 Stonedon Drive East Tamaki Auckland

Phone +64 9 274 1400 ~ Fax +64 9 274 1405

[www.polymer.co.nz](http://www.polymer.co.nz) ~ [sales@polymer.co.nz](mailto:sales@polymer.co.nz)

**Disclaimer:**

This information is provided in good faith and should be taken as a guide only. Each application will be subject to a number of variables that can affect application rates, including but not limited to, the condition of the substrate and applicator skill.