

Cleaning of Vulkem Waterproofing Membranes

To maximise the life of the waterproofing deck membrane and maintain the waterproofing warranty, regular maintenance and cleaning must be carried out. (Refer to the maintenance and inspection programme).

Cleaning the Membrane

1. Use a non-toxic household cleaning product or warm soapy water. Refer to data sheet or packaging for any dilution rates.
2. Apply to the deck and scrub with a hard bristle broom or a deck scrub, ensuring the cleaner produces a foaming action.
3. Hose or wash off the area with cold water. You can use a squeegee to assist you in this process. If using a mop, be aware that some mops may leave mop fibres in the non-slip medium.



Rev 0 Aug2022

To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to Polymer Group Ltd quality control. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of products. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY THE SELLER, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OR LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.