

Invisilink® Seam Fabric is a lightweight, yet super durable, tear resistant seam fabric. Invisilink® features stitch bonded polyester which is one of the strongest materials available to the roofing industry for use as reinforcement in cold process roofing. Invisilink®'s characteristics provide an unusual combination of high strength properties with good elongation for excellent thermal stress force accommodations. The soft polyesters will readily conform to various roof surfaces such as embedded gravel and standing seam metal roof decks. It is also much easier to handle and apply properly than other soft polyester sheets. Invisilink® is used with Undercover, WetSuit® 1-Part or WetSuit® Trowel on new construction with seams and gaps more than ¼" wide and during the rehabilitation of existing roofs.

### Technical Data

PHYSICAL PROPERTIES	ASTM TEST	RESULT
Weight		3 oz. / sq. yd.
Color		White
Tensile	ASTM D1682	57.1 lbs.
Elongation	ASTM D1682	61.65%
Mullen Burst	ASTM D3786	176.8 lbs.
Trapezoid	ASTM D117	16.1 lbs.

#### AVAILABLE SIZES

4" X 300'

6" X 300'

40" X 324'

#### Neptune Coatings Corporation

4260 Wagon Trail Ave.

Las Vegas, NV 89118

[www.neptunecoatings.com](http://www.neptunecoatings.com)

1-800-967-7659



**Neptune Coatings Corporation**  
4260 Wagon Trail Ave.  
Las Vegas, NV 89118  
[www.neptunecoatings.com](http://www.neptunecoatings.com)  
1-800-967-7659

Approved distributor of Neptune Wetsuit waterproofing products in NZ

POLYMER GROUP LTD  
62 STONEDON DRIVE  
EAST TAMAKI  
2013 AUCKLAND

T: 0800 999 001  
E: [sales@polymer.co.nz](mailto:sales@polymer.co.nz)  
[www.polymer.co.nz](http://www.polymer.co.nz)