



## Roofing and Waterproofing Patch & Reinforced Patch For Professional Use Only

### DESCRIPTION

WetSuit® Fiberated Trowel is a high viscosity, water-based coating specifically designed as a roofing and waterproofing patch. Applied by trowel or brush, it is ideal for sealing leaky roof penetrations, ducting, flashings, cracks, joints and tears. WetSuit® Fiberated Trowel is ideal on EPdM, TPO, asphalt, wood, metal, concrete and foam. Additionally, WetSuit® Fiberated Trowel can be used as a waterproofing adhesive for setting tile and stone and is a very efficient product for preparation to fill cracks, voids and as a boot for small penetrations.

WetSuit® Fiberated Trowel has been reinforced with special selected fibers which cures into a high tensile strength, minimum elongation roofing and waterproofing patch. Trowel, brush, or hand applied, it works perfectly for detailing high movement areas such as penetrations and joints.

### MAIN CHARACTERISTICS

- Water based
- No VOC's, Non-toxic
- Will not crack or peel;
- Low temperature flexibility
- Excellent adhesion
- Withstand Ponding Water

Property	Test method	Result
Color		Black or brown
Non toxic		No solvent
Shelf Life		1 year
Temperature for application		40°F to 100°F / 4.5°C to 38°C
Adhesion on Concrete before / after conditioning	AS/NZS 1580.408.5	1.75 Mpa - 254 psi / 1.87 MPa - 271 psi
Adhesion to Plywood before / after conditioning	AS/NZS 1580.408.5	Substrate integrity is weaker than adhesion
Adhesion to iron roof before / after the conditioning	AS/NZS 1580.408.5	2.80 MPa - 406 psi / 3.71 MPa - 538 psi
Adhesion to Torch membrane before / after conditioning	AS/NZS 1580.408.5	1.08 MPa - 157 psi / 1.40 MPa - 203 psi

### SURFACE PREPARATION

**General:** Surfaces to be coated should be dry, free of dust, dirt, oil, loose granules, peeling coating or other foreign matter.

### PACKAGING/SHIPPING INFORMATION

**CONTAINER SIZE**  
**CLASS**

**5 Gallon pail (18.9 liters)**

**SHIPPING**

**Class 55**

To the best of our knowledge all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. User must contact Neptune Coatings to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Neptune Coatings. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY NEPTUNE COATINGS EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Neptune Coatings  
4260 Wagon Trail Avenue  
Las Vegas NV 89118  
Tel +1 (702) 410 5500  
[info@neptunecoatings.com](mailto:info@neptunecoatings.com)

Approved distributor of Neptune Wetsuit waterproofing products in NZ  
POLYMER GROUP LTD  
62 STONEDON DRIVE  
EAST TAMAKI  
2013 AUCKLAND  
T: 0800 999 001  
E: [sales@polymer.co.nz](mailto:sales@polymer.co.nz)  
[www.polymer.co.nz](http://www.polymer.co.nz)