



# Self-leveling Cold Applied Membrane For detailing

## For Professional Use Only

### DESCRIPTION

Wetsuit® UnderCover is a water-based, medium viscosity, self-leveling, monolithic membrane that can be sprayed, brushed, or roll applied up to 80 mils wet vertically. UnderCover is used under, or between, the WetSuit® products as well as other specified Topcoats.

Wetsuit® UnderCover exhibits a tenacious adhesion to most substrates and is primarily used as detail product in conjunction with Invisilink® fabric to detail penetrations, pre-strip in joints, edging, or cant strips, or self-level areas prior to specified Topcoat application.

### MAIN CHARACTERISTICS

- Tenacious monolithic membrane;
- Use with Invisilink® for penetration and joints;
- Water based
- No VOC's, Non-toxic
- Will not crack or peel;
- Low temperature flexibility
- Excellent adhesion
- Self-Leveling

Property	Test method	Result
Color		Black or brown
Non toxic		No solvent
Shelf Life		1 year
Adhesion on Concrete before / after conditioning	AS/NZS 1580.408.5	1.62 Mpa - 234 psi / 2.22 MPa - 321 psi
Adhesion to Plywood before / after conditioning	AS/NZS 1580.408.5	Substrate integrity is weaker than adhesion
Adhesion to iron roof before / after the conditioning	AS/NZS 1580.408.5	2.53 MPa - 367 psi / 2.87 MPa - 416 psi
Adhesion to Torch membrane before / after conditioning	AS/NZS 1580.408.5	1.26 MPa - 182 psi / 1.64 MPa - 237 psi

### SURFACE PREPARATION

**General:** Surfaces to be coated should be dry, free of dust, dirt, oil, loose granules, peeling coating or other foreign matter.

### PACKAGING/SHIPPING INFORMATION

**CONTAINER SIZE** \_\_\_\_\_ **SHIPPING CLASS**

**55 Gallon drum (208.2 liters)**

**Class 55**

**5 Gallon pail (18.9 liters)**

**Class 55**

Approved distributor of Neptune Wetsuit waterproofing products in NZ

POLYMER GROUP LTD  
62 STONEDON DRIVE  
EAST TAMAKI  
2013 AUCKLAND

T: 0800 999 001  
E: sales@polymer.co.nz  
www.polymer.co.nz

To the best of our knowledge all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. User must contact Neptune Coatings to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Neptune Coatings. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY NEPTUNE COATINGS EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Neptune Coatings  
4260 Wagon Trail Avenue  
Las Vegas NV 89118  
Tel +1 (702) 410 5500  
[info@neptunecoatings.com](mailto:info@neptunecoatings.com)